


Round flow cassette

BLDC fan motor unit for ceiling mounting.
360° air discharge

- › 360° air discharge ensures uniform air flow and temperature distribution
- › Modern style decoration panel in white (RAL9010)
- › Optional fresh air intake
- › Comfortable horizontal air discharge ensures draughtfree operation and prevents ceiling soiling
- › Possibility to shut 1 or 2 flaps for easy installation in corners



FWC-BT/BF




BRC7E532F/533F



BRC315D7

- › Standard drain pump with 675mm lift increases flexibility and installation speed



			FWC-BT/BF	06	07	08	09	06	07	08	09
				2-pipe				4-pipe			
Cooling capacity (standard conditions)	Latent capacity	High	kW	1.3	1.4	1.5	1.6		1.7	1.8	1.9
	Sensible capacity	Low	kW	2.8	3.3	3.5	4.1	3.1	3.3	3.5	4.0
		Medium	kW	3.5	4.0	4.5	5.3	3.6	4.0	4.5	5.2
		High	kW	4.2	4.7	5.7	6.5	4.2	4.6	5.4	6.4
Total capacity	Low	kW	3.9	4.5	4.8	5.4	4.3	4.6	4.8	5.7	
	Medium	kW	4.7	5.3	5.9	6.8	5.1	5.6	6.2	6.9	
	High	kW	5.5	6.1	7.2	8.1	5.9	6.3	7.2	8.3	
Heating capacity (standard conditions)	Capacity	Low	kW	4.8	5.5	5.8	7.0	5.2	5.5	5.8	6.8
		Medium	kW	5.8	6.6	7.6	8.8	6.1	6.7	7.6	8.7
		High	kW	6.8	7.7	9.2	10.6	6.9	7.8	9.2	10.4
Power input		kW	0.034	0.037	0.039	0.045	0.035	0.038	0.040	0.046	
			0.040	0.046	0.058	0.076	0.041	0.047	0.059	0.077	
			0.045	0.054	0.077	0.107	0.046	0.055	0.077	0.107	
FCEER				116	119	113	104	124	120	112	106
FCCOP				143	147	141	137	149	144	138	131
Dimensions	Unit	HeightxWidthxDepth	mm	288x840x840							
Weight	Unit		kg	26							
Fan	Type			Turbo fan							
	Quantity			1							
Air flow rate	Low	m³/h	720	834	888	1,044	708	804	852	1,014	
	Medium	m³/h	894	1,038	1,200	1,410	864	1,002	1,164	1,374	
	High	m³/h	1,068	1,236	1,518	1,776	1,032	1,200	1,476	1,746	
Total sound power level	Low	dBA	31.0	33.0	36.0	40.0	33.0	36.0			40.0
	Medium	dBA	36.0	39.0	44.0	49.0	36.0	39.0	44.0	49.0	
	High	dBA	43.0	47.0	53.0	57.0	43.0	47.0	53.0	57.0	
Sound pressure level	Low	dBA	21.0	22.0	24.0	28.0	21.0	22.0	24.0	28.0	
	Medium	dBA	24.0	28.0	32.0	37.0	24.0	28.0	32.0	37.0	
	High	dBA	29.0	33.0	39.0	43.0	29.0	33.0	39.0	43.0	
Piping connections	Drain	OD	mm	VP25 (External dia.32 / internal dia. 25)							
Power supply	Phase/Frequency/Voltage	Hz/V		1~50/220-240							